

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1

(43) International Publication Date
18 October 2001 (18.10.2001)

PCT

(10) International Publication Number
WO 01/78401 A2

(51) International Patent Classification⁷: **H04N 7/24**

(71) Applicant (for all designated States except US): AMERICA ONLINE, INC. [US/US]; 22000 AOL Way, Dulles, VA 20166 (US).

(21) International Application Number: PCT/US01/11371

(22) International Filing Date: 9 April 2001 (09.04.2001)

(72) Inventors; and

(25) **Filing Language:** English

(75) **Inventors/Applicants (for US only):** **COOPER, Robert, M.** [US/US]; 4001 Lorcom Lane, Arlington, VA 22207 (US). **KJRSH, Laurence, F.** [US/US]; 695 Old Hunt Way, Herndon, VA 20170 (US). **SILVA, Carlos, A., Jr.** [US/US]; 9810 Potomac Manors Drive, Potomac, MD 20854 (US). **ESCOBAR, George, D.** [US/US]; 365 Innisbrook Circle, Purcellville, VA 20132 (US).

(26) **Publication Language:** English

(30) Priority Data:
60/195,248 7 April 2000 (07.04.2000) US


(74) Agent: RACUNAS, Robert, V., Jr.; Fish & Richardson,
601 Thirteenth Street N.W., Washington, DC 20005 (US).

(63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:
US 60/195,248 (CON)
Filed on 7 April 2000 (07.04.2000)

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM.

[Continued on next page]

(54) Title: CONTEXTUAL PROGRAMMING



(57) Abstract: Systems and techniques for providing content relevant to television programming currently displayed to a viewer by determining television programming being viewed by a viewer at a particular time; determining context information associated with the television programming available for delivery to the viewer; making an intelligent selection from the available context information; and delivering the selected context information to the viewer.



HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Contextual Programming

This application claims priority from Application No. 09/365,734, filed August 3, 1999, Application No. 09/365,735, filed August 3, 1999, and Application No. 09/475,391, filed December 30, 1999. This application also claims the benefit of Provisional Application No. 60/195,248, filed April 7, 2000. These applications are incorporated by reference in
5 their entirety.

TECHNICAL FIELD

This application relates generally to a communications system and more particularly to a communications system for providing content relevant to television programming.

BACKGROUND

Web-based TV (television) systems make dual usage of conventional television sets. That is, a user of a web-based TV system can either view television programming or access the Internet through the television set. A web-based system typically includes a device known as a set-top box, which connects to the television and translates Internet content into a
10 TV signal.
15

In general, accessing the Internet through a television set may have significant drawbacks when compared to accessing the Internet using a PC (personal computer). When set-top boxes are not equipped to function as computers, the capabilities of a web-based TV system can be quite limited. For example, while a user typically can surf to most Web sites and send e-mail, the user may not be able to display certain content, download files, or store
20 information.

SUMMARY

In one general aspect, content relevant to television programming displayed to a viewer is provided by determining television programming being viewed by a viewer at a particular time, determining context information associated with the television programming
25 available for delivery to the viewer, making an intelligent selection from the available context information, and delivering the selected context information to the viewer.

Implementations may include one or more of the following features. For example, determining the television programming being viewed by a viewer at a particular time may

be based on television programming tuned to by a set-top box or based on an electronic programming guide ("EPG"). The television programming may be a television program name or episode, a broadcaster identifier, a network identifier, a channel identification number, an EPG identifier, a program content category, or an EPG content category. The context information associated with the television programming may be determined based upon a television signal received by a set-top box, a channel identification number, a broadcaster identifier, a network identifier, a television program name or episode, an EPG identifier, a program content category, or an EPG content category. The context information may include a uniform resource locator ("URL"), such as a shopping website, a new website, a viewer polling website, an advertising website, a webpage registered with an online service provider ("OSP"), an OSP partner-programmed web page. The context information also may include advertising, an online chat room, an instant messaging buddy list, news, a merchandise purchasing opportunity, and/or a viewer poll.

An intelligent selection may be made from among the available context information based upon a predetermined hierarchy, a viewer determined hierarchy, or a dynamically determined hierarchy. For example, the hierarchy may be determined by an episode or name of a television program, a broadcaster identifier, a network identifier, a content category, an EPG category, and/or an EPG identifier. In one implementation, the context information is first selected based upon an episode of a television program. If no context information based upon the episode is found, the context information is selected based upon a name of the television program. If no context information based upon the name of the television program is found, the context information is selected based upon a broadcaster identifier. If no context information based upon a broadcaster identifier is found, the context information is selected based upon a content category.

The selected context information may be delivered to the viewer by a set-top box displaying the information on the viewer's monitor or television screen. Typically, the selected context information is displayed along with the television programming. A television signal containing the television programming may be received, and the television signal may contain the context information. The context information may be received during the vertical blanking interval of the television signal.

The context information may be determined while the viewer is offline or online. The context information accessed by the viewer may be tracked and reported.

In another general aspect, a system that provides content relevant to television programming may have a set-top box with communications links for receiving context information, a television signal containing television programming, or both. A monitor displays the received television programming and context information. Software instructions stored within the set-top box provide content relevant to the television programming and cause the context information to be displayed along with the television programming. Implementations may include a television signal that contains the television programming and the context information. The context information may be received during the vertical blanking interval of the television signal.

In another general aspect, a graphical user interface provides content relevant to television programming through an area designated for display of television programming and an area designated for display of context information associated with the television programming.

These and other aspects may be implemented by an apparatus and/or a computer program stored on a computer readable medium. The computer readable medium may be a disc, a client device, a host device, and/or a propagated signal.

Other features and advantages will be apparent from the following description, including the drawings, and the claims.

DESCRIPTION OF DRAWINGS

Fig. 1 is a block diagram of a web-based TV system.

Fig. 2 is a block diagram of a set-top box system.

Figs. 3 and 4 are flow charts of communications methods that may be implemented by the systems of Fig. 1 and Fig. 2.

Figs. 5-8 are screen shots that may be used to deliver contextual information and television programming to viewers.

Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION

An exemplary web-based TV system 100 is shown in Fig. 1. The system 100 includes a set-top box 20 connected to a video display device 10. The video display device 10 may be implemented using, for example, an analog TV, a digital TV, a high definition TV (HDTV), a video monitor, or another device capable of displaying analog and/or digital video signals. The set-top box 20 gathers and manages content for presentation on the video display device 10.

The set-top box 20 gathers and manages two primary types of content: web content and TV content. Web content includes, for example, digital information that is typically, but not exclusively, communicated over a communications network. Examples of web content include: a web page, an image file, an audio file, a video file, a data file, a program, an e-mail message, an instant message, and a chat session. TV content may include digital and analog information intended for presentation on a video display device that generally corresponds to established standards, such as, for example, European Telecommunications Standards Institute (ETSI), Digital Video Broadcasting (DVB), Advanced Television Systems Committee (ATSC), or European Cable Communications Association (ECCA). Examples of TV content include a broadcast TV program, a satellite TV program, a cable TV program, an output of a video player/recorder device, such as, for example, a videocassette recorder (VCR), a laser disc player, and a digital videodisk (DVD) player, and output of a video camera.

The set-top box 20 may use any of a variety of known methods to gather web and TV content. The set-top box 20 can be configured to receive web content from sources, such as an ultra high frequency (UHF) or a very high frequency (VHF) transmitter, a digital transmitter, a radio frequency (RF) transmitter, a satellite transmitter, a cable TV provider, and the Internet. For example, the set-top box 20 can access web content over the Internet through a connection to an Internet Service Provider (ISP) or host 35, such as America Online or CompuServe. The set-top box 20 connects to the host 35 through a communications link 37 (e.g., a plain old telephone service (POTS), a digital subscriber line (DSL), or an integrated systems digital network (ISDN)) typically provided by a telecommunications company. Once connected to the host 35, the set-top box 20 can gather web content from any number of content providers 40 connected to the Internet 30. The set-

top box 20 also can access web content from a satellite 50. The satellite 50 receives the web content from an uplink 55 provided by a transmitter 57 connected to, for example, the host 35. The web content is provided to the set-top box 20 through a downlink 58 from the satellite 50 to a receiving dish 59. Similarly, the set-top box 20 may receive web content
5 through a cable communications link 60 connected to a cable company 61. Furthermore, web content may be inserted in the vertical blanking interval (VBI) of a TV signal (e.g. broadcast, cable, or satellite). A description of using the VBI to send web content to the set-top box 20 is included in U.S. Application No. 09/584,347 filed June 1, 2000, titled "Online/Offline Triggers," which is incorporated herein by reference in its entirety.

10 The set-top box 20 may receive TV content from a number of sources. For example, a TV station 70 can broadcast UHF or VHF TV signals 71 from a TV transmitter tower 72. The TV signals 71 are received by an antenna 73 connected to the set-top box 20. Likewise, a TV programming distribution service 80 (e.g., Direct TV™) can transmit TV content from a transmitter 85 to a satellite 87 for transmission to a receiving dish 59 connected to the set-top
15 box 20. TV content also may be provided directly to the set-top box 20 from the cable company 61 by cable communications link 60.

Fig. 2 shows an example of a set-top box system 200 that includes a set-top box 20. The set-top box 20 includes a tuner 201 that may receive quadrature amplitude modulation (QAM), orthogonal frequency division multiplexing (OFDM), and quadrature phase shift key
20 (QPSK) digital TV signals 210. The digital TV signals 210 are received by the tuner 201 from components of a system 100, such as, for example, a cable communications link 61, or a satellite dish 57. Similarly, analog TV signals 211 are provided to the tuner 201 using components of the system 100, such as, for example, antenna 73. The tuner 201 may be implemented using a broadcast in-band tuner, an out-of-band tuner, and a return path tuner.
25 In addition, the TV tuner 201 may receive TV signals 210 or 211 from a video recorder/player device (e.g., a VCR, a DVD player, and a laser disc player). A separate interface also may be provided for receiving these signals (as described in detail below). The tuner 201 isolates a physical channel from the received signal 210 or 211 and converts it to a baseband signal.

30 The baseband signal output from the tuner 201 is sent to a demodulator 215. The demodulator 215 samples an analog signal and converts it to a digital bit-stream (e.g.,

Moving Pictures Experts Group (MPEG)-2 bit stream). The data may be organized in discrete units that may be referred to as data packets. The bit-stream may include video, audio, and other data. The bit-stream is checked for errors and is forwarded to a decrypting unit 220. The decrypting unit 220 examines the packets in the bit-stream, selects particular packets, decrypts the selected packets, and forwards the decrypted packets to one or more of a video decoder 225, an audio decoder 226, or a data decoder 227.

The video decoder 225 transforms video packets into a sequence of pictures that may be displayed on the display device 10. The output from the video decoder 225 can be sent to an optional graphics processor 228 for enhanced TV and web content display. If a graphics processor is not included, the output of the video decoder 225 is sent directly to the system bus 229. The system bus 229 provides a communications path between the processor 240 and the various components of the set-top box 20. An audio decoder 226 decompresses an audio bit-stream for delivery to a speaker 230 or to the system bus 229. The data decoder 227 is connected to the system bus 229 and decodes data packets for processing by the processor 240.

The processor 240 operates according to any number of available operating systems available from, for example, Power TV, VxWorks, pSOSystem, Microware, Microsoft, Java, or Linux. The processor 240 provides a number of functions for the set-top box 20. For example, the processor 240 initializes the set-top hardware, monitors and manages hardware interrupts, and fetches data and instructions from memory. The processor 240 also processes a range of web and TV content data. Likewise, the processor 240 may execute various programs and applications, for example, a browser, stored in the memory or storage of the set-top box 20.

The set-top box 20 may include a number of memories. For example, a random access memory (RAM) can be used as a temporary storage area for data flowing between the processor 240 and set top hardware. Both dynamic RAM (DRAM) 260 and static RAM (SRAM) 261 may be used. However, the DRAM 260 typically is used for interactive applications while the SRAM 261 may be used to support time sensitive applications, such as MPEG processing. Read only memory (ROM), such as an electrically erasable programming ROM (EEPROM) 262 and a flash memory 263, also may be provided. The EEPROM 262 is used to store control programs and boot-up information for the processor 240. The flash

memory 263 may be used to store programs and customer specific information. The flash memory 263 also may be used to store data downloaded from the host 35 that provide, for example, new or additional functionality to the set-top box 20, temporary data or data that are continually updated. The set-top box 20 also may include a large-scale memory device, such as a hard drive 265. The hard drive 265 may be used to store TV and web content, such as, for example, personal documents, favorite Internet sites, email, recorded TV content, data files, audio files, video files, programs, and other data.

The set-top box 20 may include a number of input/output (I/O) interfaces 270 including: a modem 271, a high-speed multimedia interface 272, a serial interface 273, a common interface 274, a TV and VCR interface 275, and wireless interfaces 276 to devices, such as a remote control 280 and a wireless keyboard 281. The set-top box also may include a smart card reader 290. The I/O interfaces provide a communications path between external devices and the system bus 229 to facilitate the exchange of data with the set-top box 20. The set-top box 20 may include one or more of any of these interfaces.

The modem 271 facilitates two-way interactivity between the set-top box 20 and the host 35 or a service provider (e.g., cable company 61). Once activated, the modem 271 can send a request to a web server on the Internet 30, and may enable a viewer to download a file, to send an e-mail message, and to facilitate two-way interactive services, such as home shopping or video-on-demand.

The high-speed multimedia interface 272 allows the set-top box 20 to communicate in real time with other devices, such as a camcorder, a DVD player, a laser disk player, a CD player, and a digital camera. The high-speed interface 272 may be implemented using various hardware devices, such as, for example, an IEEE 1284 parallel port, a universal serial bus, and a 10/100 Base-T (i.e., Ethernet).

The serial interface 273, which may be, for example, an RS-232 interface, provides a serial communications interface that allows the set-top box 20 to exchange data with other devices, such as, for example, a printer, a computer, a personal data assistant (PDA), or an external storage device.

The common interface 274 may be included to provide a standardized interface to connect the set-top box 20 with a separate hardware module, such as a PCMCIA interface.

The TV and VCR interface 275 allows the set-top box 20 to communicate with the display device 10 and a video recorder/player.

Wireless interfaces 276 receive control signals from a user interface device, such as, for example, a wireless keyboard device 280 and a remote control device 281. The control signals are interpreted by processor 240 to activate and control functions of the set-top box 20 and the display device 10. The remote control interface 276 can communicate with the devices 20 using RF signals, infrared signals, or otherwise.

Smart card reader 290 may read a smart card that contains, for example, identification information for authorizing access to the host 35, a service, or an e-commerce transaction.

The set-top box 20 constructs or formats a display for presentation on a screen of the display device 10. The display may be constructed from web content, TV content, or a combination of both web and TV content. A browser (e.g., Liberate's TV navigator) running by the set top processor 240 creates the display from outputs of the memories (e.g., 260, 261, and 262), the hard disk 265, the I/O interfaces 270, and/or the decoders (i.e., 225, 226, and 227). The browser can support a number of computing standards including, for example, hypertext markup language (HTML), JavaScript, and hypertext transfer protocol (HTTP).

The browser integrates web and TV content by processing, for example, a window tag. A widow tag is an HTML-like tag (e.g.,) that instructs the browser to place TV content received by the set-top box 20 on the screen of the display device 10 at specified coordinates. By modifying a received web page to include a window tag, the browser can display the TV content in conjunction with web content in windows for each type of content. Any number of content windows may be displayed on a screen at one time. In addition, the windows may be separate or may appear to overlap each other. Web content also can be assigned HTML-like tags indicating the arrangement of the web content on the screen. The screen of the display device 10 can be modified to insert user controls, resize the TV image, and provide interactive links by altering instructions of the web content displayed by the browser.

In addition, the set-top box 20 may present content that is overlaid with user interface controls or menus. The controls and menus correspond to functions performed by the set-top box 20, such as, tuning channels. Interactive controls and display windows also may appear as overlaying the TV content or web content on the screen of the display device 10.

Providing content relevant to television programming currently displayed to a viewer, through an intelligent selection, assumes the existence of television programming and available context information. The television programming may be, for example, an episode of a television show. A television show may be broadcast by a particular broadcaster (e.g.,
5 network, cable company) during a particular time slot and shown on a particular channel. A television show may be mapped by a host, for example, to a particular category of an EPG. The host may map and/or otherwise classify television programming based on content, television show, episode, broadcaster, channel, time slot, or other criteria.

Context information includes contextual chat rooms, an implementation of which is
10 described in patent application Serial No. 09/475,391, filed December 30, 1999, and titled "Television Chat Rooms." Context information also includes electronic pages served from servers within an online service provider host complex and/or the Internet. Authors, such as, for example, broadcasters and other interested parties (e.g., business partners, venders, promoters) and/or their agents can create electronic pages using HTML, JavaScript, and/or
15 other markup language. Electronic pages may be published and accessible through online service providers, the World Wide Web, and/or the Internet.

Contextual electronic pages may include episode-specific pages such as, for example, interactive event pages relating to a current episode; an electronic message board to post and read messages about a current episode; electronic viewer polls for soliciting and tallying
20 opinions from viewers; links or pages having episodic tie-ins for retrieving further information about features of an episode; special previews of future episodes; and/or community applications such as chat rooms, interest groups, and instant messaging buddy lists for communicating with other viewers about the current episode. Contextual electronic pages also may include show specific pages such as, for example, an episode guide
25 containing information about past episodes; a cast information page providing information about persons appearing in the show; community applications for discussing past, present and future episodes; and shopping pages for enabling viewers to purchase items featured in the television show, items of a show sponsor, and/or items affiliated with viewer demographics of the television show. In one implementation, contextual shopping pages
30 allow viewers to receive purchasing information about items appearing in a television broadcast by positioning a cursor and/or clicking displayed items. Purchasing information

may include price, manufacturer, retailer, in-stock availability, shipping schedule, and/or any other ordering information.

Contextual electronic pages may further include broadcaster-specific pages such as, for example, a complete listing of shows televised by the broadcaster; promotions for
5 interactive events; and/or an electronic portal to websites of business partners and/or advertisers. Additionally, the electronic pages may include content-category-specific pages related to the EPG content category of the television programming and/or the EPG program description.

An exemplary process 300 for making context information available to viewers is
10 shown in Fig. 3. In this example, context information includes one or more published electronic pages related to television programming. Initially, context information (e.g., an electronic page) is created (step 302). The host may facilitate creation and/or publication of electronic pages by establishing a predetermined and approved style. The host may, for
15 example, provide a page template to business partners. Electronic pages created with the template may be displayed within a host-branded frame and may contain elements programmed and served by the host, including, but not limited to, HTML links, graphics, promotions and/or advertising. The author of the electronic page may, and is expected to, include additional functionality and programming beyond that provided by the template and/or frame.

20 In one implementation, the host manages the registration of context information by associating electronic pages with television programming. After creating and optionally publishing the electronic page, the author (e.g., business partner) submits the electronic page to the host for registration (step 304). Prior to registering the electronic page, the host reviews the electronic page (step 306). The review may include examining the electronic
25 page for approved functionality and adherence to style. The electronic page also may be reviewed by an outside agency for appropriateness. The host may refuse to register any page that does not conform to a particular style or that violates the host's publication policy.

After being approved, the context information is then registered (step 308). In one
30 implementation, the host registers content and/or a storage location (e.g., URL) of an electronic page. Registration of published electronic pages may be implemented by associating the electronic page with television programming. In particular, the electronic

page may be associated with the name of a particular television show, a certain episode of a television show, a television broadcaster, a content category, a time slot, and/or any other identifier of television programming. In one example, the host enters context information associated with a specific television show into a table assigned for maintaining data related to the specific television show. The data in the table is made available to viewers during the broadcast of the television programming.

Newly registered context information is added and/or assigned to television programming on a regularly scheduled basis. The host may track and report user traffic to registered pages. Such tracking and reporting may be done for customer satisfaction and/or cost analysis. Even after registration, context information may be subjected to viewing policies and may be restricted by filtering settings. Registered pages may be deregistered for violations of the viewing policies or for departure from the style guidelines. Deregistered context information may be removed at any time.

Fig. 4 is a flowchart showing an example of the steps involved in a generalized process 400 for providing content relevant to television programming currently displayed to a viewer. The process 400 may be implemented, for example, by the web-based TV system 100 and/or the set-top box system 200, described above.

In one implementation, the process 400 is initiated by a viewer of a particular television program. To begin the process 400, the viewer may, for example, select a menu option, click a displayed icon or hyperlink, type a particular keyword, and/or push a designated button on a remote control. Upon initiation of the process 400, the television programming being viewed by a viewer at a particular time is determined (step 402). The set-top box and/or host may determine the television programming of a viewer in conjunction with or independently from each other. Implementations of determining the current television programming may include, for example, detecting the channel to which the set-top box is tuned, sampling and/or retrieving embedded information from a television signal corresponding to the television programming, determining the current broadcaster of the television programming, determining the television show and/or episode, and/or determining the EPG category associated with the television programming. Other implementations may involve determining information about the viewer such as, for example, the viewer's local time, gender, age, and interests. In one such possible implementation, the viewer may have

previously specified that the News Channel should be presented to that viewer using a "sports context" -- e.g., the News Channel content page will emphasize or give priority to news features or headlines that relate to sports.

After having determined the television programming being viewed by the viewer (step 402), context information associated with the television programming available for delivery to the viewer is determined (step 404). The context information can be retrieved whether the set-top box is in an online or offline state, and can come either from local sources (e.g., information previously received and stored in the set-top box) or from remote sources (e.g., host computer or VBI) or a combination of both.

In one implementation, the viewer's set-top box receives and references context information associated with television programming. Referencing the context information associated with television programming may be done in any way that enables searching and retrieval. In one implementation, the viewer's set-top box references the context information according to episode, television show, broadcaster, time slot, and/or content category of the television programming. Relevant information about the television programming can be extracted from the television signal and/or determined from the viewer's EPG.

The set-top box can obtain the context information on-the-fly directly from the host, provided the set-top box is logged into the host at that time. Alternatively, or in addition, the set-top box can retrieve locally stored information, e.g., from the set-top box's internal memory or from storage media such as a cassette tape or CD-ROM loaded into a peripheral device connected to the set-top box. This locally stored information will have been downloaded previously and cached by the set-top box for future use. Retrieval of locally stored information is always available, whether the viewer is offline or online.

Context and/or other information can be communicated to the set-top box for storage and subsequent retrieval using any of several different methods. One available technique is to "trickle-down" information from the host to the set-top box in the background (i.e., transparently to, and without being requested by, the viewer) while the viewer is connected to the host. This trickled-down information then is stored by the set-top box so that it is available for future use, such as, for example, if the viewer, while offline, requests a content page requiring context information.

An alternative mechanism for communicating context or other information to the set-

top box involves the use of VBIs (Vertical Blanking Intervals) in TV frames. The standard NTSC TV signal used in the United States is made up of "frames" that are broadcast at a rate of 30 each second. Each frame is formed of 525 scan lines divided equally into two separate and contiguous fields, field 1 and field 2. Each field includes 262.5 scan lines, 241.5 of which carry visible TV signal information - that is, portions of the TV picture.

The first 21 lines in each field represent the VBI. The VBI corresponds to the period of time that it takes the electron beam emitted by the TV set's cathode ray tube (CRT) to reposition itself from the bottom of the TV screen to the top of the screen (also referred to "vertical retracing"). After each field is received and displayed, the electron beam must be repositioned in this manner before drawing of the first scan line of the next field may commence. Accordingly, no visible TV signal information can be transmitted during the VBI, since such visible TV signal information would be lost. Instead, basically any other type of information may be transmitted to the set-top box and used for various purposes, such as, for example, closed captioning, teletext, and electronic program guide information. The amount of data that can be transmitted in this manner is roughly equal to the capacity of a 9600 baud modem for each available scan line in the VBI.

Accordingly, in one implementation, context information can be communicated directly from the TV broadcaster to a set-top box within the VBIs of a TV signal. For each TV field received, the set-top box can extract the context information from the VBI and use it to generate various elements of a content page. The VBI can be used in this regard either in real or near real time (i.e., the context information in the VBI can be extracted and used by the set-top box immediately upon receipt) or the VBI can be used to trickle-down information to the set-top box for storage and subsequent retrieval, as described above.

Other mechanisms for communicating context information to the set-top box include sending data using satellite communications -- for example, similar to messages in a pager or Personal Communication Services (PCS) network -- and/or an "always connected" technology such as Digital Subscriber Lines (DSL). In either case, the context information received by the set-top box either can be used immediately or stored for subsequent use.

Caching context information and/or other content in the set-top box as described above reduces the demands on the host computer system and on the communication link connecting the host system to the set-top box. For example, viewers need not be logged into

the host system in order to be able to view context information. As a result, because viewers can remain logged off the host system for much, if not all, of the viewing session, the number of terminal servers or other connection ports that the host system needs to maintain can be reduced. At the same time, the viewer's telephone line, or other communication medium
5 connecting the viewer to the outside world, need not always be connected to the host system and thus can be freed up for other uses.

Once the available context information is determined (step 404), an intelligent selection from the available context information is made (step 406). In one implementation, an intelligent selecting is made according to a context hierarchy. For example, television
10 programming may include an episode of a television show including certain content and broadcast by a particular broadcaster. According to one context searching hierarchy, first a search is performed for context information associated with the episode (e.g., season finale, particular NFL football game) (step 406a). If episode context information is found, it is selected. If no episode context information is found and/or available, then a search is
15 performed for context information associated with the television show (e.g., name of sitcom, NFL football) (step 406b). If show context information is found, it is selected. If no show context is found and/or available, then a search is performed for context information associated with the broadcaster (e.g., particular network station, cable station) (step 406c). If broadcaster context information is found, it is selected. If no broadcaster context information
20 is found and/or available, default content contextual information (e.g., Networks, Sports) is selected.

According to the above context searching hierarchy, searching for context information associated with a particular broadcaster should only take place if no context information is found to be associated with the episode and television show. Likewise,
25 content channel page context information is used only if no television show or broadcaster context information is found.

In another implementation, an intelligent selection of available context information is performed according to a hierarchy selected by the viewer. In yet another implementation, the hierarchy is selected by the content provider or the broadcaster. In another
30 implementation, the hierarchy is determined based upon user preferences as determined, for example, from information about the viewer such as, for example, the viewer's geographic

location, local time, gender, age, and interests. In a further implementation, the hierarchy is not fixed, but rather is dynamic and may be modified at any time.

Finally, the selected context information is delivered to the viewer (step 408). In one implementation, an electronic page associated with the currently viewed television show,
5 episode, broadcaster, timeslot, and/or EPG content category is served to the set-top box of the viewer.

If, for example, the context information served to the set-top box of the viewer is a shopping opportunity related to the episode of the TV show being watched by the viewer, the viewer may decide to purchase the displayed merchandise. To purchase the merchandise, the
10 viewer would designate the merchandise to be purchased using, for example, a wireless keyboard 280 or remote control device 281. The viewer may also provide a credit card number, or, in other approaches, a credit card number may be on file with the host, or the item may be added to the viewer's account with the host, or the viewer may insert a smart card into a smart card reader 290 to facilitate the transaction. Also, the viewer may purchase
15 items related to the TV show by using the wireless keyboard 280 or remote control device 281 to point to the item featured in the TV show and click or otherwise designate the item to be purchased.

Fig. 5 is one example of an episode-specific page 500 that may be used to present context information to a viewer. The page 500 is an interactive event page includes an area:
20 505 for displaying a television broadcast and an area 510 for displaying context information. In this example, the context information includes a question box, an electronic ballot for soliciting questions and opinions from viewers, and links to poll results and a chat room.

Fig. 6 is on example of a show-specific page 600 that may be used to present context information to a viewer. The page 600 includes an area 605 for displaying a television
25 broadcast and an area 610 for displaying context information. In this example, the contextual information includes further information about a featured television show and a link for ordering merchandise associated with the television show.

Fig. 7 is on example of a broadcaster-specific page 700 that may be used to present context information to a viewer. The page 700 includes an area 705 for displaying a
30 television broadcast and an area 710 for displaying context information. In this example, the

contextual information includes further information about a featured televised news story and links to a broadcaster's optimized home page as well as websites of business partners.

Fig. 8 is an example of a category-specific page 800 that may be used to present context information to a viewer. The page 800 includes an area 805 for displaying a television broadcast and an area 810 for displaying context information. In this example, the contextual information includes links related to category content, i.e., music.

A number of implementations have been described. Nevertheless, it will be understood that various modifications may be made. Accordingly, other embodiments are within the scope of the following claims.

WHAT IS CLAIMED IS:

- 1 1. A method of providing content relevant to television programming, the
2 method comprising:
3 determining television programming being viewed by a viewer at a particular time;
4 determining context information associated with the television programming
5 available for delivery to the viewer;
6 making an intelligent selection from the available context information; and
7 delivering the selected context information to the viewer.
- 1 2. The method of claim 1 wherein determining television programming being
2 viewed comprises determining the television programming tuned to by a set-top box.
- 1 3. The method of claim 1 wherein determining television programming being
2 viewed comprises determining the television programming based upon an EPG.
- 1 4. The method of claim 1 wherein determining context information associated
2 with the television programming comprises determining context information based upon a
3 television signal received by a set-top box.
- 1 5. The method of claim 1 wherein determining context information associated
2 with the television programming comprises determining context information based upon a
3 channel identification number.
- 1 6. The method of claim 1 wherein determining context information associated
2 with the television programming comprises determining context information based upon a
3 broadcaster identifier.
- 1 7. The method of claim 1 wherein determining context information associated
2 with the television programming comprises determining context information based upon a
3 television show.

1 8. The method of claim 1 wherein determining context information associated
2 with the television programming comprises determining context information based upon an
3 episode of a television show.

1 9. The method of claim 1 wherein determining context information associated
2 with the television programming comprises determining context information based upon an
3 EPG identifier.

1 10. The method of claim 1 wherein determining context information associated
2 with the television programming comprises determining context information based upon a
3 program content category.

1 11. The method of claim 1 wherein making an intelligent selection comprises
2 selecting context information based upon a predetermined hierarchy.

1 12. The method of claim 11 wherein the hierarchy is determined by an episode of
2 a television program.

1 13. The method of claim 11 wherein the hierarchy is determined by a television
2 program.

1 14. The method of claim 11 wherein the hierarchy is determined by a broadcaster
2 identifier.

1 15. The method of claim 11 wherein the hierarchy is determined by an EPG
2 identifier.

1 16. The method of claim 11 wherein the hierarchy comprises:
2 first selecting context information based upon an episode of a television
3 program;

4 where no context information based upon an episode is found, selecting
5 context information based upon a television program;

6 where no context information based upon a television program is found,
7 selecting context information based upon a broadcaster identifier; and

8 where no context information based upon a broadcaster identifier is found,
9 selecting context information based upon a content category.

1 17. The method of claim 1 wherein making an intelligent selection comprises
2 selecting context information based upon a viewer selected hierarchy.

1 18. The method of claim 1 wherein making an intelligent selection comprises
2 selecting context information based upon a dynamically determined hierarchy.

1 19. The method of claim 1 wherein delivering the selected context information to
2 the viewer comprises displaying the context information by a set-top box.

1 20. A computer program, stored on a computer readable medium, comprising
2 instructions for causing a computer system to perform the following operations:
3 determine television programming being viewed by a viewer at a particular time;
4 determine context information associated with the television programming available
5 for delivery to the viewer;
6 make an intelligent selection from the available context information; and
7 deliver the selected context information to the viewer.

1 21. The computer program of claim 20 wherein the computer readable medium is a
2 disc.

1 22. The computer program of claim 20 wherein the computer readable medium is a
2 client device.

1 23. The computer program of claim 20 wherein the computer readable medium is a
2 host device.

1 24. The computer program of claim 20 wherein the computer readable medium is a
2 propagated signal.

1




FIG. 1




FIG. 2





FIG. 3



S00


AOLTV

II Poll Poll P

How can Jordan rebuild the Wizards?

- Change coach
- Trade players
- Spend time with the team
- Get support from fans

Cast Your Vote



Tonight's Guest:
Michael Jordan

ASK YOUR QUESTION NOW!

Ask Larry

Larry King Live Poll Results

Chat About Larry King

S10

Fig. S

600

AOLTV


NETWORKS

*Airs: March 6
10 a.m., 4 p.m.*

**TRUE
HOLLYWOOD
STORY**

Networks

It's been a wild, roller-coaster affair with fame for Burt Reynolds. He went from gridiron star at Florida State University to movie star in Hollywood. But he's also endured a debilitating drug dependency and one of the messiest divorce...



**E! Big E!
T-shirt**

In Stock?

Call 1-800-858-1111

600

605

Fig. 6

700



710

Fig. 7

800

805

AOLTV

music

TELLING
STORIES

Telling Stories


Telling Stories gives

★★★


NEWS

MUSIC

search



Find an artist
or album



Marc Anthony
The Latin Heartthrob
performs "I Need to Know"
on Saturday Night Live
NBC, Saturday 11:30 PM

New Neil Young Album Set for April Release

810

Fig 8

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 October 2001 (18.10.2001)

PCT

(10) International Publication Number
WO 01/78401 A3

(51) International Patent Classification⁷: H04N 7/16, 7/173

(21) International Application Number: PCT/US01/11371

(22) International Filing Date: 9 April 2001 (09.04.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/195,248 7 April 2000 (07.04.2000) US

(63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:

US 60/195,248 (CON)
Filed on 7 April 2000 (07.04.2000)

(71) Applicant (for all designated States except US): AMERICA ONLINE, INC. [US/US]: 22000 AOL Way, Dulles, VA 20166 (US).

(72) Inventors: and


(75) Inventors/Applicants (for US only): COOPER, Robert, M. [US/US]: 4001 Lorcom Lane, Arlington, VA 22207 (US). KIRSII, Laurence, F. [US/US]: 695 Old Hunt Way, Herndon, VA 20170 (US). SILVA, Carlos, A., Jr. [US/US]: 9810 Potomac Manors Drive, Potomac, MD 20854 (US). ESCOBAR, George, D. [US/US]: 365 Innisbrook Circle, Purcellville, VA 20132 (US).

(74) Agent: RACUNAS, Robert, V., Jr.; Fish & Richardson, 601 Thirteenth Street N.W., Washington, DC 20005 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

[Continued on next page]

(54) Title: CONTEXTUAL PROGRAMMING



(57) Abstract: Systems and techniques for providing content relevant to television programming currently displayed to a viewer by determining television programming being viewed by a viewer at a particular time; determining context information associated with the television programming available for delivery to the viewer; making an intelligent selection from the available context information; and delivering the selected context information to the viewer.



(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(88) **Date of publication of the international search report:**

7 February 2002

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/11371

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 H04N7/16 H04N7/173

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

WPI Data, EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 774 664 A (HIDARY JACK D ET AL) 30 June 1998 (1998-06-30)	1
A	column 2, line 21 - line 26	2-24
Y	US 5 929 849 A (KIKINIS DAN) 27 July 1999 (1999-07-27)	1, 20
A	the whole document	2-19, 21-24
Y	US 5 861 906 A (DUNN MATTHEW W ET AL) 19 January 1999 (1999-01-19)	1
A	the whole document	2-24
Y	US 5 663 757 A (MORALES FERNANDO) 2 September 1997 (1997-09-02)	20
A	abstract	1-19, 21-24
	--- -/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

23 August 2001

Date of mailing of the international search report

04/09/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Greve, M

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/11371

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 559 549 A (BONNER ALFRED E ET AL) 24 September 1996 (1996-09-24) the whole document ---	1-24
A	WO 98 37696 A (HERZ FREDERICK S M) 27 August 1998 (1998-08-27) abstract ---	1-24
A	US 5 798 785 A (BONNER ALFRED E ET AL) 25 August 1998 (1998-08-25) the whole document ---	1-24
A	WO 99 09744 A (SONY ELECTRONICS INC) 25 February 1999 (1999-02-25) page 2, line 12 -page 3, line 12 ---	1-24
A	WO 99 04561 A (SCHOAFF P CHRISTOPHER ;ALEXANDER RON (US); GUIDE E INC (US); HANCO) 28 January 1999 (1999-01-28) the whole document -----	1-24

INTERNATIONAL SEARCH REPORT

Int'l Application No

PCT/US 01/11371

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5774664 A	30-06-1998	US 5778181 A AT 204110 T AU 2070597 A EP 0885525 A EP 0982943 A WO 9733434 A US 6018768 A	07-07-1998 15-08-2001 22-09-1997 23-12-1998 01-03-2000 12-09-1997 25-01-2000
US 5929849 A	27-07-1999	CN 1221538 A EP 0896774 A JP 11510978 T WO 9741690 A	30-06-1999 17-02-1999 21-09-1999 06-11-1997
US 5861906 A	19-01-1999	NONE	
US 5663757 A	02-09-1997	US 5036389 A US 5101267 A US 5392353 A AU 634242 B AU 5693790 A CA 2018539 A CN 1048136 A, B CS 9002906 A EP 0402809 A IE 902108 A IL 94519 A JP 3064286 A NO 176299 B NZ 233837 A PT 94361 A US 5257099 A US 5223923 A	30-07-1991 31-03-1992 21-02-1995 18-02-1993 20-12-1990 13-12-1990 26-12-1990 12-11-1991 19-12-1990 02-01-1991 08-07-1993 19-03-1991 28-11-1994 28-04-1992 31-12-1991 26-10-1993 29-06-1993
US 5559549 A	24-09-1996	US 6052554 A AT 177277 T AT 199294 T AT 176840 T AT 192005 T AT 190180 T AT 183352 T AT 176841 T AT 197366 T AU 715683 B AU 4440797 A AU 712157 B AU 4532597 A AU 693775 B AU 5732994 A AU 692427 B AU 5733094 A AU 691479 B AU 5733194 A AU 692428 B AU 5733294 A AU 5736394 A AU 5845894 A AU 5869894 A AU 716184 B	18-04-2000 15-03-1999 15-03-2001 15-03-1999 15-05-2000 15-03-2000 15-08-1999 15-03-1999 15-11-2000 10-02-2000 29-01-1998 28-10-1999 05-02-1998 09-07-1998 04-07-1994 11-06-1998 04-07-1994 21-05-1998 04-07-1994 11-06-1998 04-07-1994 04-07-1994 22-06-1994 04-07-1994 24-02-2000

INTERNATIONAL SEARCH REPORT

Int. Application No.

PCT/US 01/11371

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5559549 A		AU 6066798 A	04-06-1998
		AU 716182 B	24-02-2000
		AU 6066898 A	04-06-1998
		BR 9307619 A	15-06-1999
		BR 9307620 A	10-08-1999
		BR 9307621 A	15-06-1999
		BR 9307622 A	15-06-1999
		BR 9307623 A	16-05-2000
		BR 9307624 A	15-06-1999
		BR 9307625 A	31-08-1999
		CA 2151456 A	23-06-1994
		CA 2151457 A	23-06-1994
		CA 2151458 A	23-06-1994
		CA 2151459 A	23-06-1994
		CA 2151460 A	23-06-1994
		CA 2151461 A	09-06-1994
		CA 2151462 A	23-06-1994
		CN 1259826 A	12-07-2000
		CN 1259827 A	12-07-2000
		CN 1276682 A	13-12-2000
		CN 1276683 A	13-12-2000
		CN 1276684 A	13-12-2000
		CN 1276685 A	13-12-2000
		CN 1284814 A	21-02-2001
WO 9837696 A	27-08-1998	AU 6175198 A	09-09-1998
		EP 0962098 A	08-12-1999
US 5798785 A	25-08-1998	AT 197659 T	15-12-2000
		AU 1333795 A	19-06-1995
		AU 693148 B	25-06-1998
		AU 1430695 A	19-06-1995
		BR 9408211 A	26-08-1997
		CA 2177153 A	08-06-1995
		CA 2177154 A	08-06-1995
		DE 69426308 D	21-12-2000
		DE 69426308 T	21-06-2001
		EP 0732027 A	18-09-1996
		EP 0732031 A	18-09-1996
		EP 0963116 A	08-12-1999
		ES 2151590 T	01-01-2001
		JP 9506225 T	17-06-1997
		JP 9510327 T	14-10-1997
		NZ 278185 A	27-04-1998
		WO 9515649 A	08-06-1995
		WO 9515658 A	08-06-1995
		US 6201536 B	13-03-2001
		AT 177277 T	15-03-1999
		AT 199294 T	15-03-2001
		AT 176840 T	15-03-1999
		AT 192005 T	15-05-2000
		AT 190180 T	15-03-2000
		AT 183352 T	15-08-1999
		AT 176841 T	15-03-1999
		AT 197366 T	15-11-2000
		AU 715683 B	10-02-2000
		AU 4440797 A	29-01-1998
		AU 712157 B	28-10-1999

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/11371

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5798785 A		AU 4532597 A	05-02-1998
		AU 693775 B	09-07-1998
		AU 5732994 A	04-07-1994
		AU 692427 B	11-06-1998
		AU 5733094 A	04-07-1994
		AU 691479 B	21-05-1998
		AU 5733194 A	04-07-1994
		AU 692428 B	11-06-1998
		AU 5733294 A	04-07-1994
		AU 5736394 A	04-07-1994
		AU 5845894 A	22-06-1994
		AU 5869894 A	04-07-1994
		AU 716184 B	24-02-2000
		AU 6066798 A	04-06-1998
		AU 716182 B	24-02-2000
		AU 6066898 A	04-06-1998
		BR 9307619 A	15-06-1999
		BR 9307620 A	10-08-1999
WO 9909744 A	25-02-1999	AU 8689598 A	08-03-1999
WO 9904561 A	28-01-1999	AU 733993 B	31-05-2001
		AU 8504898 A	10-02-1999
		BR 9812104 A	18-07-2000
		CN 1290452 T	04-04-2001
		EP 1036466 A	20-09-2000
		US 6122011 A	19-09-2000
		US 6177931 B	23-01-2001
		US 6217435 B	17-04-2001

THIS PAGE BLANK (USPTO)

CORRECTED VERSION

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 October 2001 (18.10.2001)

PCT

(10) International Publication Number
WO 01/078401 A3

(51) International Patent Classification⁷: H04N 7/16, 7/173

(21) International Application Number: PCT/US01/11371

(22) International Filing Date: 9 April 2001 (09.04.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/195,248 7 April 2000 (07.04.2000) US

(63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:
US 60/195,248 (CON)
Filed on 7 April 2000 (07.04.2000)

(71) Applicant (for all designated States except US): AMERICA ONLINE, INC. [US/US]; 22000 AOL Way, Dulles, VA 20166 (US).


(72) Inventors; and

(75) Inventors/Applicants (for US only): COOPER, Robert, M. [US/US]; 4001 Lorcom Lane, Arlington, VA 22207 (US). KIRSH, Laurence, F. [US/US]; 695 Old Hunt Way, Herndon, VA 20170 (US). SILVA, Carlos, A., Jr. [US/US]; 9810 Potomac Manors Drive, Potomac, MD 20854 (US). ESCOBAR, George, D. [US/US]; 365 Innisbrook Circle, Purcellville, VA 20132 (US).

(74) Agent: RACUNAS, Robert, V., Jr.; Fish & Richardson_P.C., 1425 K Street, N.W., 11th Floor, Washington_DC 20005-3500 (US).

[Continued on next page]

(54) Title: CONTEXTUAL PROGRAMMING



(57) Abstract: Systems and techniques for providing content relevant to television programming currently displayed to a viewer by determining television programming being viewed by a viewer at a particular time; determining context information associated with the television programming available for delivery to the viewer; making an intelligent selection from the available context information; and delivering the selected context information to the viewer.



WO 01/078401 A3



(81) **Designated States (national):** AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(84) **Designated States (regional):** ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

(88) **Date of publication of the international search report:**

7 February 2002

(48) **Date of publication of this corrected version:**

19 December 2002

(15) **Information about Correction:**

see PCT Gazette No. 51/2002 of 19 December 2002, Section II

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Contextual Programming

This application claims priority from Application No. 09/365,734, filed August 3, 1999, Application No. 09/365,735, filed August 3, 1999, and Application No. 09/475,391, filed December 30, 1999. This application also claims the benefit of Provisional Application No. 60/195,248, filed April 7, 2000. These applications are incorporated by reference in
5 their entirety.

TECHNICAL FIELD

This application relates generally to a communications system and more particularly to a communications system for providing content relevant to television programming.

BACKGROUND

Web-based TV (television) systems make dual usage of conventional television sets. That is, a user of a web-based TV system can either view television programming or access the Internet through the television set. A web-based system typically includes a device known as a set-top box, which connects to the television and translates Internet content into a
10 TV signal.
15

In general, accessing the Internet through a television set may have significant drawbacks when compared to accessing the Internet using a PC (personal computer). When set-top boxes are not equipped to function as computers, the capabilities of a web-based TV system can be quite limited. For example, while a user typically can surf to most Web sites and send e-mail, the user may not be able to display certain content, download files, or store
20 information.

SUMMARY

In one general aspect, content relevant to television programming displayed to a viewer is provided by determining television programming being viewed by a viewer at a
25 particular time, determining context information associated with the television programming available for delivery to the viewer, making an intelligent selection from the available context information, and delivering the selected context information to the viewer.

Implementations may include one or more of the following features. For example, determining the television programming being viewed by a viewer at a particular time may

be based on television programming tuned to by a set-top box or based on an electronic programming guide ("EPG"). The television programming may be a television program name or episode, a broadcaster identifier, a network identifier, a channel identification number, an EPG identifier, a program content category, or an EPG content category. The context information associated with the television programming may be determined based upon a television signal received by a set-top box, a channel identification number, a broadcaster identifier, a network identifier, a television program name or episode, an EPG identifier, a program content category, or an EPG content category. The context information may include a uniform resource locator ("URL"), such as a shopping website, a new website, a viewer polling website, an advertising website, a webpage registered with an online service provider ("OSP"), an OSP partner-programmed web page. The context information also may include advertising, an online chat room, an instant messaging buddy list, news, a merchandise purchasing opportunity, and/or a viewer poll.

An intelligent selection may be made from among the available context information based upon a predetermined hierarchy, a viewer determined hierarchy, or a dynamically determined hierarchy. For example, the hierarchy may be determined by an episode or name of a television program, a broadcaster identifier, a network identifier, a content category, an EPG category, and/or an EPG identifier. In one implementation, the context information is first selected based upon an episode of a television program. If no context information based upon the episode is found, the context information is selected based upon a name of the television program. If no context information based upon the name of the television program is found, the context information is selected based upon a broadcaster identifier. If no context information based upon a broadcaster identifier is found, the context information is selected based upon a content category.

The selected context information may be delivered to the viewer by a set-top box displaying the information on the viewer's monitor or television screen. Typically, the selected context information is displayed along with the television programming. A television signal containing the television programming may be received, and the television signal may contain the context information. The context information may be received during the vertical blanking interval of the television signal.

The context information may be determined while the viewer is offline or online. The context information accessed by the viewer may be tracked and reported.

In another general aspect, a system that provides content relevant to television programming may have a set-top box with communications links for receiving context
5 information, a television signal containing television programming, or both. A monitor displays the received television programming and context information. Software instructions stored within the set-top box provide content relevant to the television programming and cause the context information to be displayed along with the television programming. Implementations may include a television signal that contains the television programming
10 and the context information. The context information may be received during the vertical blanking interval of the television signal.

In another general aspect, a graphical user interface provides content relevant to television programming through an area designated for display of television programming and an area designated for display of context information associated with the television
15 programming.

These and other aspects may be implemented by an apparatus and/or a computer program stored on a computer readable medium. The computer readable medium may be a disc, a client device, a host device, and/or a propagated signal.

Other features and advantages will be apparent from the following description,
20 including the drawings, and the claims.

DESCRIPTION OF DRAWINGS

Fig. 1 is a block diagram of a web-based TV system.

Fig. 2 is a block diagram of a set-top box system.

Figs. 3 and 4 are flow charts of communications methods that may be implemented
25 by the systems of Fig. 1 and Fig. 2.

Figs. 5-8 are screen shots that may be used to deliver contextual information and television programming to viewers.

Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION

An exemplary web-based TV system 100 is shown in Fig. 1. The system 100 includes a set-top box 20 connected to a video display device 10. The video display device 10 may be implemented using, for example, an analog TV, a digital TV, a high definition TV (HDTV), a video monitor, or another device capable of displaying analog and/or digital video signals. The set-top box 20 gathers and manages content for presentation on the video display device 10.

The set-top box 20 gathers and manages two primary types of content: web content and TV content. Web content includes, for example, digital information that is typically, but not exclusively, communicated over a communications network. Examples of web content include: a web page, an image file, an audio file, a video file, a data file, a program, an e-mail message, an instant message, and a chat session. TV content may include digital and analog information intended for presentation on a video display device that generally corresponds to established standards, such as, for example, European Telecommunications Standards Institute (ETSI), Digital Video Broadcasting (DVB), Advanced Television Systems Committee (ATSC), or European Cable Communications Association (ECCA). Examples of TV content include a broadcast TV program, a satellite TV program, a cable TV program, an output of a video player/recorder device, such as, for example, a videocassette recorder (VCR), a laser disc player, and a digital videodisk (DVD) player, and output of a video camera.

The set-top box 20 may use any of a variety of known methods to gather web and TV content. The set-top box 20 can be configured to receive web content from sources, such as an ultra high frequency (UHF) or a very high frequency (VHF) transmitter, a digital transmitter, a radio frequency (RF) transmitter, a satellite transmitter, a cable TV provider, and the Internet. For example, the set-top box 20 can access web content over the Internet through a connection to an Internet Service Provider (ISP) or host 35, such as America Online or CompuServe. The set-top box 20 connects to the host 35 through a communications link 37 (e.g., a plain old telephone service (POTS), a digital subscriber line (DSL), or an integrated systems digital network (ISDN)) typically provided by a telecommunications company. Once connected to the host 35, the set-top box 20 can gather web content from any number of content providers 40 connected to the Internet 30. The set-

top box 20 also can access web content from a satellite 50. The satellite 50 receives the web content from an uplink 55 provided by a transmitter 57 connected to, for example, the host 35. The web content is provided to the set-top box 20 through a downlink 58 from the satellite 50 to a receiving dish 59. Similarly, the set-top box 20 may receive web content through a cable communications link 60 connected to a cable company 61. Furthermore, web content may be inserted in the vertical blanking interval (VBI) of a TV signal (e.g. broadcast, cable, or satellite). A description of using the VBI to send web content to the set-top box 20 is included in U.S. Application No. 09/584,347 filed June 1, 2000, titled "Online/Offline Triggers," which is incorporated herein by reference in its entirety.

The set-top box 20 may receive TV content from a number of sources. For example, a TV station 70 can broadcast UHF or VHF TV signals 71 from a TV transmitter tower 72. The TV signals 71 are received by an antenna 73 connected to the set-top box 20. Likewise, a TV programming distribution service 80 (e.g., Direct TV™) can transmit TV content from a transmitter 85 to a satellite 87 for transmission to a receiving dish 59 connected to the set-top box 20. TV content also may be provided directly to the set-top box 20 from the cable company 61 by cable communications link 60.

Fig. 2 shows an example of a set-top box system 200 that includes a set-top box 20. The set-top box 20 includes a tuner 201 that may receive quadrature amplitude modulation (QAM), orthogonal frequency division multiplexing (OFDM), and quadrature phase shift key (QPSK) digital TV signals 210. The digital TV signals 210 are received by the tuner 201 from components of a system 100, such as, for example, a cable communications link 61, or a satellite dish 57. Similarly, analog TV signals 211 are provided to the tuner 201 using components of the system 100, such as, for example, antenna 73. The tuner 201 may be implemented using a broadcast in-band tuner, an out-of-band tuner, and a return path tuner. In addition, the TV tuner 201 may receive TV signals 210 or 211 from a video recorder/player device (e.g., a VCR, a DVD player, and a laser disc player). A separate interface also may be provided for receiving these signals (as described in detail below). The tuner 201 isolates a physical channel from the received signal 210 or 211 and converts it to a baseband signal.

The baseband signal output from the tuner 201 is sent to a demodulator 215. The demodulator 215 samples an analog signal and converts it to a digital bit-stream (e.g.,

Moving Pictures Experts Group (MPEG)-2 bit stream). The data may be organized in discrete units that may be referred to as data packets. The bit-stream may include video, audio, and other data. The bit-stream is checked for errors and is forwarded to a decrypting unit 220. The decrypting unit 220 examines the packets in the bit-stream, selects particular
5 packets, decrypts the selected packets, and forwards the decrypted packets to one or more of a video decoder 225, an audio decoder 226, or a data decoder 227.

The video decoder 225 transforms video packets into a sequence of pictures that may be displayed on the display device 10. The output from the video decoder 225 can be sent to an optional graphics processor 228 for enhanced TV and web content display. If a graphics
10 processor is not included, the output of the video decoder 225 is sent directly to the system bus 229. The system bus 229 provides a communications path between the processor 240 and the various components of the set-top box 20. An audio decoder 226 decompresses an audio bit-stream for delivery to a speaker 230 or to the system bus 229. The data decoder 227 is connected to the system bus 229 and decodes data packets for processing by the
15 processor 240.

The processor 240 operates according to any number of available operating systems available from, for example, Power TV, VxWorks, pSOSystem, Microware, Microsoft, Java, or Linux. The processor 240 provides a number of functions for the set-top box 20. For example, the processor 240 initializes the set-top hardware, monitors and manages hardware
20 interrupts, and fetches data and instructions from memory. The processor 240 also processes a range of web and TV content data. Likewise, the processor 240 may execute various programs and applications, for example, a browser, stored in the memory or storage of the set-top box 20.

The set-top box 20 may include a number of memories. For example, a random
25 access memory (RAM) can be used as a temporary storage area for data flowing between the processor 240 and set top hardware. Both dynamic RAM (DRAM) 260 and static RAM (SRAM) 261 may be used. However, the DRAM 260 typically is used for interactive applications while the SRAM 261 may be used to support time sensitive applications, such as MPEG processing. Read only memory (ROM), such as an electrically erasable programming
30 ROM (EEPROM) 262 and a flash memory 263, also may be provided. The EEPROM 262 is used to store control programs and boot-up information for the processor 240. The flash

memory 263 may be used to store programs and customer specific information. The flash memory 263 also may be used to store data downloaded from the host 35 that provide, for example, new or additional functionality to the set-top box 20, temporary data or data that are continually updated. The set-top box 20 also may include a large-scale memory device, such as a hard drive 265. The hard drive 265 may be used to store TV and web content, such as, for example, personal documents, favorite Internet sites, email, recorded TV content, data files, audio files, video files, programs, and other data.

The set-top box 20 may include a number of input/output (I/O) interfaces 270 including: a modem 271, a high-speed multimedia interface 272, a serial interface 273, a common interface 274, a TV and VCR interface 275, and wireless interfaces 276 to devices, such as a remote control 280 and a wireless keyboard 281. The set-top box also may include a smart card reader 290. The I/O interfaces provide a communications path between external devices and the system bus 229 to facilitate the exchange of data with the set-top box 20. The set-top box 20 may include one or more of any of these interfaces.

The modem 271 facilitates two-way interactivity between the set-top box 20 and the host 35 or a service provider (e.g., cable company 61). Once activated, the modem 271 can send a request to a web server on the Internet 30, and may enable a viewer to download a file, to send an e-mail message, and to facilitate two-way interactive services, such as home shopping or video-on-demand.

The high-speed multimedia interface 272 allows the set-top box 20 to communicate in real time with other devices, such as a camcorder, a DVD player, a laser disk player, a CD player, and a digital camera. The high-speed interface 272 may be implemented using various hardware devices, such as, for example, an IEEE 1284 parallel port, a universal serial bus, and a 10/100 Base-T (i.e., Ethernet).

The serial interface 273, which may be, for example, an RS-232 interface, provides a serial communications interface that allows the set-top box 20 to exchange data with other devices, such as, for example, a printer, a computer, a personal data assistant (PDA), or an external storage device.

The common interface 274 may be included to provide a standardized interface to connect the set-top box 20 with a separate hardware module, such as a PCMCIA interface.

The TV and VCR interface 275 allows the set-top box 20 to communicate with the display device 10 and a video recorder/player.

Wireless interfaces 276 receive control signals from a user interface device, such as, for example, a wireless keyboard device 280 and a remote control device 281. The control signals are interpreted by processor 240 to activate and control functions of the set-top box 20 and the display device 10. The remote control interface 276 can communicate with the devices 20 using RF signals, infrared signals, or otherwise.

Smart card reader 290 may read a smart card that contains, for example, identification information for authorizing access to the host 35, a service, or an e-commerce transaction.

The set-top box 20 constructs or formats a display for presentation on a screen of the display device 10. The display may be constructed from web content, TV content, or a combination of both web and TV content. A browser (e.g., Liberate's TV navigator) running by the set top processor 240 creates the display from outputs of the memories (e.g., 260, 261, and 262), the hard disk 265, the I/O interfaces 270, and/or the decoders (i.e., 225, 226, and 227). The browser can support a number of computing standards including, for example, hypertext markup language (HTML), JavaScript, and hypertext transfer protocol (HTTP).

The browser integrates web and TV content by processing, for example, a window tag. A widow tag is an HTML-like tag (e.g.,) that instructs the browser to place TV content received by the set-top box 20 on the screen of the display device 10 at specified coordinates. By modifying a received web page to include a window tag, the browser can display the TV content in conjunction with web content in windows for each type of content. Any number of content windows may be displayed on a screen at one time. In addition, the windows may be separate or may appear to overlap each other. Web content also can be assigned HTML-like tags indicating the arrangement of the web content on the screen. The screen of the display device 10 can be modified to insert user controls, resize the TV image, and provide interactive links by altering instructions of the web content displayed by the browser.

In addition, the set-top box 20 may present content that is overlaid with user interface controls or menus. The controls and menus correspond to functions performed by the set-top box 20, such as, tuning channels. Interactive controls and display windows also may appear as overlaying the TV content or web content on the screen of the display device 10.

Providing content relevant to television programming currently displayed to a viewer, through an intelligent selection, assumes the existence of television programming and available context information. The television programming may be, for example, an episode of a television show. A television show may be broadcast by a particular broadcaster (e.g.,
5 network, cable company) during a particular time slot and shown on a particular channel. A television show may be mapped by a host, for example, to a particular category of an EPG. The host may map and/or otherwise classify television programming based on content, television show, episode, broadcaster, channel, time slot, or other criteria.

Context information includes contextual chat rooms, an implementation of which is
10 described in patent application Serial No. 09/475,391, filed December 30, 1999, and titled "Television Chat Rooms." Context information also includes electronic pages served from servers within an online service provider host complex and/or the Internet. Authors, such as, for example, broadcasters and other interested parties (e.g., business partners, venders, promoters) and/or their agents can create electronic pages using HTML, JavaScript, and/or
15 other markup language. Electronic pages may be published and accessible through online service providers, the World Wide Web, and/or the Internet.

Contextual electronic pages may include episode-specific pages such as, for example, interactive event pages relating to a current episode; an electronic message board to post and read messages about a current episode; electronic viewer polls for soliciting and tallying
20 opinions from viewers; links or pages having episodic tie-ins for retrieving further information about features of an episode; special previews of future episodes; and/or community applications such as chat rooms, interest groups, and instant messaging buddy lists for communicating with other viewers about the current episode. Contextual electronic pages also may include show specific pages such as, for example, an episode guide
25 containing information about past episodes; a cast information page providing information about persons appearing in the show; community applications for discussing past, present and future episodes; and shopping pages for enabling viewers to purchase items featured in the television show, items of a show sponsor, and/or items affiliated with viewer demographics of the television show. In one implementation, contextual shopping pages
30 allow viewers to receive purchasing information about items appearing in a television broadcast by positioning a cursor and/or clicking displayed items. Purchasing information

may include price, manufacturer, retailer, in-stock availability, shipping schedule, and/or any other ordering information.

Contextual electronic pages may further include broadcaster-specific pages such as, for example, a complete listing of shows televised by the broadcaster; promotions for
5 interactive events; and/or an electronic portal to websites of business partners and/or advertisers. Additionally, the electronic pages may include content-category-specific pages related to the EPG content category of the television programming and/or the EPG program description.

An exemplary process 300 for making context information available to viewers is
10 shown in Fig. 3. In this example, context information includes one or more published electronic pages related to television programming. Initially, context information (e.g., an electronic page) is created (step 302). The host may facilitate creation and/or publication of electronic pages by establishing a predetermined and approved style. The host may, for
15 example, provide a page template to business partners. Electronic pages created with the template may be displayed within a host-branded frame and may contain elements programmed and served by the host, including, but not limited to, HTML links, graphics, promotions and/or advertising. The author of the electronic page may, and is expected to, include additional functionality and programming beyond that provided by the template and/or frame.

20 In one implementation, the host manages the registration of context information by associating electronic pages with television programming. After creating and optionally publishing the electronic page, the author (e.g., business partner) submits the electronic page to the host for registration (step 304). Prior to registering the electronic page, the host reviews the electronic page (step 306). The review may include examining the electronic
25 page for approved functionality and adherence to style. The electronic page also may be reviewed by an outside agency for appropriateness. The host may refuse to register any page that does not conform to a particular style or that violates the host's publication policy.

After being approved, the context information is then registered (step 308). In one
30 implementation, the host registers content and/or a storage location (e.g., URL) of an electronic page. Registration of published electronic pages may be implemented by associating the electronic page with television programming. In particular, the electronic

page may be associated with the name of a particular television show, a certain episode of a television show, a television broadcaster, a content category, a time slot, and/or any other identifier of television programming. In one example, the host enters context information associated with a specific television show into a table assigned for maintaining data related to the specific television show. The data in the table is made available to viewers during the broadcast of the television programming.

Newly registered context information is added and/or assigned to television programming on a regularly scheduled basis. The host may track and report user traffic to registered pages. Such tracking and reporting may be done for customer satisfaction and/or cost analysis. Even after registration, context information may be subjected to viewing policies and may be restricted by filtering settings. Registered pages may be deregistered for violations of the viewing policies or for departure from the style guidelines. Deregistered context information may be removed at any time.

Fig. 4 is a flowchart showing an example of the steps involved in a generalized process 400 for providing content relevant to television programming currently displayed to a viewer. The process 400 may be implemented, for example, by the web-based TV system 100 and/or the set-top box system 200, described above.

In one implementation, the process 400 is initiated by a viewer of a particular television program. To begin the process 400, the viewer may, for example, select a menu option, click a displayed icon or hyperlink, type a particular keyword, and/or push a designated button on a remote control. Upon initiation of the process 400, the television programming being viewed by a viewer at a particular time is determined (step 402). The set-top box and/or host may determine the television programming of a viewer in conjunction with or independently from each other. Implementations of determining the current television programming may include, for example, detecting the channel to which the set-top box is tuned, sampling and/or retrieving embedded information from a television signal corresponding to the television programming, determining the current broadcaster of the television programming, determining the television show and/or episode, and/or determining the EPG category associated with the television programming. Other implementations may involve determining information about the viewer such as, for example, the viewer's local time, gender, age, and interests. In one such possible implementation, the viewer may have

previously specified that the News Channel should be presented to that viewer using a "sports context" -- e.g., the News Channel content page will emphasize or give priority to news features or headlines that relate to sports.

After having determined the television programming being viewed by the viewer (step 402), context information associated with the television programming available for delivery to the viewer is determined (step 404). The context information can be retrieved whether the set-top box is in an online or offline state, and can come either from local sources (e.g., information previously received and stored in the set-top box) or from remote sources (e.g., host computer or VBI) or a combination of both.

In one implementation, the viewer's set-top box receives and references context information associated with television programming. Referencing the context information associated with television programming may be done in any way that enables searching and retrieval. In one implementation, the viewer's set-top box references the context information according to episode, television show, broadcaster, time slot, and/or content category of the television programming. Relevant information about the television programming can be extracted from the television signal and/or determined from the viewer's EPG.

The set-top box can obtain the context information on-the-fly directly from the host, provided the set-top box is logged into the host at that time. Alternatively, or in addition, the set-top box can retrieve locally stored information, e.g., from the set-top box's internal memory or from storage media such as a cassette tape or CD-ROM loaded into a peripheral device connected to the set-top box. This locally stored information will have been downloaded previously and cached by the set-top box for future use. Retrieval of locally stored information is always available, whether the viewer is offline or online.

Context and/or other information can be communicated to the set-top box for storage and subsequent retrieval using any of several different methods. One available technique is to "trickle-down" information from the host to the set-top box in the background (i.e., transparently to, and without being requested by, the viewer) while the viewer is connected to the host. This trickled-down information then is stored by the set-top box so that it is available for future use, such as, for example, if the viewer, while offline, requests a content page requiring context information.

An alternative mechanism for communicating context or other information to the set-

top box involves the use of VBIs (Vertical Blanking Intervals) in TV frames. The standard NTSC TV signal used in the United States is made up of "frames" that are broadcast at a rate of 30 each second. Each frame is formed of 525 scan lines divided equally into two separate and contiguous fields, field 1 and field 2. Each field includes 262.5 scan lines, 241.5 of which carry visible TV signal information - that is, portions of the TV picture.

The first 21 lines in each field represent the VBI. The VBI corresponds to the period of time that it takes the electron beam emitted by the TV set's cathode ray tube (CRT) to reposition itself from the bottom of the TV screen to the top of the screen (also referred to "vertical retracing"). After each field is received and displayed, the electron beam must be repositioned in this manner before drawing of the first scan line of the next field may commence. Accordingly, no visible TV signal information can be transmitted during the VBI, since such visible TV signal information would be lost. Instead, basically any other type of information may be transmitted to the set-top box and used for various purposes, such as, for example, closed captioning, teletext, and electronic program guide information. The amount of data that can be transmitted in this manner is roughly equal to the capacity of a 9600 baud modem for each available scan line in the VBI.

Accordingly, in one implementation, context information can be communicated directly from the TV broadcaster to a set-top box within the VBIs of a TV signal. For each TV field received, the set-top box can extract the context information from the VBI and use it to generate various elements of a content page. The VBI can be used in this regard either in real or near real time (i.e., the context information in the VBI can be extracted and used by the set-top box immediately upon receipt) or the VBI can be used to trickle-down information to the set-top box for storage and subsequent retrieval, as described above.

Other mechanisms for communicating context information to the set-top box include sending data using satellite communications -- for example, similar to messages in a pager or Personal Communication Services (PCS) network -- and/or an "always connected" technology such as Digital Subscriber Lines (DSL). In either case, the context information received by the set-top box either can be used immediately or stored for subsequent use.

Caching context information and/or other content in the set-top box as described above reduces the demands on the host computer system and on the communication link connecting the host system to the set-top box. For example, viewers need not be logged into

the host system in order to be able to view context information. As a result, because viewers can remain logged off the host system for much, if not all, of the viewing session, the number of terminal servers or other connection ports that the host system needs to maintain can be reduced. At the same time, the viewer's telephone line, or other communication medium
5 connecting the viewer to the outside world, need not always be connected to the host system and thus can be freed up for other uses.

Once the available context information is determined (step 404), an intelligent selection from the available context information is made (step 406). In one implementation, an intelligent selecting is made according to a context hierarchy. For example, television
10 programming may include an episode of a television show including certain content and broadcast by a particular broadcaster. According to one context searching hierarchy, first a search is performed for context information associated with the episode (e.g., season finale, particular NFL football game) (step 406a). If episode context information is found, it is selected. If no episode context information is found and/or available, then a search is
15 performed for context information associated with the television show (e.g., name of sitcom, NFL football) (step 406b). If show context information is found, it is selected. If no show context is found and/or available, then a search is performed for context information associated with the broadcaster (e.g., particular network station, cable station) (step 406c). If broadcaster context information is found, it is selected. If no broadcaster context information
20 is found and/or available, default content contextual information (e.g., Networks, Sports) is selected.

According to the above context searching hierarchy, searching for context information associated with a particular broadcaster should only take place if no context information is found to be associated with the episode and television show. Likewise,
25 content channel page context information is used only if no television show or broadcaster context information is found.

In another implementation, an intelligent selection of available context information is performed according to a hierarchy selected by the viewer. In yet another implementation, the hierarchy is selected by the content provider or the broadcaster. In another
30 implementation, the hierarchy is determined based upon user preferences as determined, for example, from information about the viewer such as, for example, the viewer's geographic

location, local time, gender, age, and interests. In a further implementation, the hierarchy is not fixed, but rather is dynamic and may be modified at any time.

Finally, the selected context information is delivered to the viewer (step 408). In one implementation, an electronic page associated with the currently viewed television show, episode, broadcaster, timeslot, and/or EPG content category is served to the set-top box of the viewer.

If, for example, the context information served to the set-top box of the viewer is a shopping opportunity related to the episode of the TV show being watched by the viewer, the viewer may decide to purchase the displayed merchandise. To purchase the merchandise, the viewer would designate the merchandise to be purchased using, for example, a wireless keyboard 280 or remote control device 281. The viewer may also provide a credit card number, or, in other approaches, a credit card number may be on file with the host, or the item may be added to the viewer's account with the host, or the viewer may insert a smart card into a smart card reader 290 to facilitate the transaction. Also, the viewer may purchase items related to the TV show by using the wireless keyboard 280 or remote control device 281 to point to the item featured in the TV show and click or otherwise designate the item to be purchased.

Fig. 5 is one example of an episode-specific page 500 that may be used to present context information to a viewer. The page 500 is an interactive event page includes an area 505 for displaying a television broadcast and an area 510 for displaying context information. In this example, the context information includes a question box, an electronic ballot for soliciting questions and opinions from viewers, and links to poll results and a chat room.

Fig. 6 is an example of a show-specific page 600 that may be used to present context information to a viewer. The page 600 includes an area 605 for displaying a television broadcast and an area 610 for displaying context information. In this example, the contextual information includes further information about a featured television show and a link for ordering merchandise associated with the television show.

Fig. 7 is an example of a broadcaster-specific page 700 that may be used to present context information to a viewer. The page 700 includes an area 705 for displaying a television broadcast and an area 710 for displaying context information. In this example, the

contextual information includes further information about a featured televised news story and links to a broadcaster's optimized home page as well as websites of business partners.

Fig. 8 is an example of a category-specific page 800 that may be used to present context information to a viewer. The page 800 includes an area 805 for displaying a television broadcast and an area 810 for displaying context information. In this example, the contextual information includes links related to category content, i.e., music.

A number of implementations have been described. Nevertheless, it will be understood that various modifications may be made. Accordingly, other embodiments are within the scope of the following claims.

WHAT IS CLAIMED IS:

1 1. A method of providing content relevant to television programming, the
2 method comprising:
3 determining television programming being viewed by a viewer at a particular time;
4 determining context information associated with the television programming
5 available for delivery to the viewer;
6 making an intelligent selection from the available context information; and
7 delivering the selected context information to the viewer.

1 2. The method of claim 1 wherein determining television programming being
2 viewed comprises determining the television programming tuned to by a set-top box.

1 3. The method of claim 1 wherein determining television programming being
2 viewed comprises determining the television programming based upon an EPG.

1 4. The method of claim 1 wherein determining context information associated
2 with the television programming comprises determining context information based upon a
3 television signal received by a set-top box.

1 5. The method of claim 1 wherein determining context information associated
2 with the television programming comprises determining context information based upon a
3 channel identification number.

1 6. The method of claim 1 wherein determining context information associated
2 with the television programming comprises determining context information based upon a
3 broadcaster identifier.

1 7. The method of claim 1 wherein determining context information associated
2 with the television programming comprises determining context information based upon a
3 television show.

1 8. The method of claim 1 wherein determining context information associated
2 with the television programming comprises determining context information based upon an
3 episode of a television show.

1 9. The method of claim 1 wherein determining context information associated
2 with the television programming comprises determining context information based upon an
3 EPG identifier.

1 10. The method of claim 1 wherein determining context information associated
2 with the television programming comprises determining context information based upon a
3 program content category.

1 11. The method of claim 1 wherein making an intelligent selection comprises
2 selecting context information based upon a predetermined hierarchy.

1 12. The method of claim 11 wherein the hierarchy is determined by an episode of
2 a television program.

1 13. The method of claim 11 wherein the hierarchy is determined by a television
2 program.

1 14. The method of claim 11 wherein the hierarchy is determined by a broadcaster
2 identifier.

1 15. The method of claim 11 wherein the hierarchy is determined by an EPG
2 identifier.

1 16. The method of claim 11 wherein the hierarchy comprises:
2 first selecting context information based upon an episode of a television
3 program;

4 where no context information based upon an episode is found, selecting
5 context information based upon a television program;
6 where no context information based upon a television program is found,
7 selecting context information based upon a broadcaster identifier; and
8 where no context information based upon a broadcaster identifier is found,
9 selecting context information based upon a content category.

1 17. The method of claim 1 wherein making an intelligent selection comprises
2 selecting context information based upon a viewer selected hierarchy.

1 18. The method of claim 1 wherein making an intelligent selection comprises
2 selecting context information based upon a dynamically determined hierarchy.

1 19. The method of claim 1 wherein delivering the selected context information to
2 the viewer comprises displaying the context information by a set-top box.

1 20. A computer program, stored on a computer readable medium, comprising
2 instructions for causing a computer system to perform the following operations:
3 determine television programming being viewed by a viewer at a particular time;
4 determine context information associated with the television programming available
5 for delivery to the viewer;
6 make an intelligent selection from the available context information; and
7 deliver the selected context information to the viewer.

1 21. The computer program of claim 20 wherein the computer readable medium is a
2 disc.

1 22. The computer program of claim 20 wherein the computer readable medium is a
2 client device.

1 23. The computer program of claim 20 wherein the computer readable medium is a
2 host device.

1 24. The computer program of claim 20 wherein the computer readable medium is a
2 propagated signal.

1




FIG. 1




FIG. 2





FIG. 3



500




FIG. 5

600




FIG. 6




FIG. 7

800




FIG. 8